

Conex Compression

A range of Compression fittings.



Features and Benefits:

- Conex Compression fittings are compatible with EN1057 equivalent copper tube to EN1057.
- Conex Compression fittings are suitable for connecting polybutylene pipes (PB) and PEX to EN15876-2, EN15875-2 and BS57291:2 and 3.
- Fittings compatible with PB and PEX pipes are available in dimensions 10,15,18,22 and 28mm.
- Used in plumbing, heating, cooling, compressed air and gas applications.
- They are manufactured in duplex brass. Many items are also available in dezincification resistance (DZR) brass.
- Manufactures in accordance with EN 1252-2 and threaded connection to EN1254-4.
- Suitable for Flame Free installations.
- PTFE tape is not required for installation.
- Installation with PB and PEX pipe requires liners recommended by the tube manufacturer or supplied by IBP.
- Imperial tube sizes can be connected with special rings and adapters.



Conex Compression

A range of Conex Compression fittings

<p>Straight Coupler</p>  <p>301 (S301) From: 6mm To: 108mm</p>	<p>Reduced Straight Coupler</p>  <p>301 RED (S301 RED) From: 8 x 6mm To: 35 x 28mm</p>	<p>Straight Coupler Bulkhead</p>  <p>301BH From: 15mm To: 15mm</p>	<p>Cross Over</p>  <p>301CO From: 15mm To: 22mm</p>	<p>Straight Coupler with Drain Tap</p>  <p>301DA From: 15mm To: 22mm</p>	<p>Imperial to Metric Straight Coupler</p>  <p>301IM From: 76 x 3" To: 76 x 3"</p>	<p>Straight Coupler with Air Vent</p>  <p>301V From: 15mm To: 15mm</p>
<p>Straight Coupler Burst pipe Repair</p>  <p>301BP From: 12mm To: 22mm</p>	<p>Male Straight Coupler</p>  <p>302 (S302) From: 6 x 1/8" To: 108 x 4"</p>	<p>Extended Male Straight Connector with Back Nut</p>  <p>302B (S302B) From: 15 x 1/2" To: 76 x 3"</p>	<p>Extended Male Straight Connector with Back Nut</p>  <p>302CB From: 15 x 1/2" x 38 To: 15 x 1/2" x 38</p>	<p>Male Taper Straight Connector</p>  <p>302TA (S302TA) From: 10 x 3/8" To: 28mm</p>	<p>Straight Tap Connector</p>  <p>303SF (S303SF) From: 15 x 1/2" To: 22 x 3/4"</p>	<p>Female Straight Connector for Pillar Tap</p>  <p>303ST From: 15mm To: 22mm</p>
<p>Tank Connector</p>  <p>321 (S321) From: 15mm To: 54mm</p>	<p>Elbow</p>  <p>401 (S401) From: 6mm To: 76mm</p>	<p>Reduced Elbow</p>  <p>401 RED (S401RED) From: 12 x 10mm To: 28 x 22mm</p>	<p>Elbow with Drain Tap</p>  <p>401DA From: 15mm To: 28mm</p>	<p>Obtuse Elbow</p>  <p>401/O From: 15mm To: 28mm</p>	<p>Slow Bend</p>  <p>S401S From: 15mm To: 28mm</p>	<p>Elbow with Air vent</p>  <p>401V From: 15mm To: 22mm</p>
<p>Male Elbow</p>  <p>402 (S402) From: 8 x 1/4" To: 54 x 2"</p>	<p>Male Elbow with Drain Tap</p>  <p>402DA From: 15 x 1/2" To: 22 x 3/4"</p>	<p>Male Taper Elbow</p>  <p>402TA (S402TA) From: 12 x 3/8" To: 28 x 1"</p>	<p>Female Elbow</p>  <p>403 (S403) From: 8 x 1/4" To: 54 x 2"</p>	<p>Bent Tap Connector</p>  <p>403SF (S403SF) From: 15 x 1/2" To: 22 x 3/4"</p>	<p>Female Wall Plate Elbow 2 Hole Flange</p>  <p>403W (S403W) From: 12 x 1/2" To: 15 x 1/2"</p>	<p>Female Wall Plate Elbow 3 Hole Flange</p>  <p>403WL (S403WL) From: 10 x 1/2" To: 22 x 3/4"</p>
<p>Tee - Equal</p>  <p>601EQ (S601EQ) From: 6mm To: 76mm</p>	<p>Tee - Reduced Branch</p>  <p>601RB (S601RB) From: 12 x 12 x 10mm To: 76 x 76 x 54mm</p>	<p>Tee - Reduced End</p>  <p>601REB (S601REB) From: 15 x 12 x 12mm To: 28 x 22 x 22mm</p>	<p>Tee - Reduced Both Ends</p>  <p>601REE (S601REE) From: 15 x 15 x 22mm To: 22 x 22 x 28mm</p>	<p>Tee with Male Branch</p>  <p>S615 From: 15 x 15 x 1/2" To: 28 x 28 x 1"</p>	<p>Tee with Female Branch</p>  <p>617 (S617) From: 12 x 12 x 3/8" To: 28 x 28 x 1"</p>	<p>Wall Plate Tee with Female Branch</p>  <p>S617W From: 15 x 15 x 1/2" To: 22 x 22 x 1/2"</p>
<p>Tee with Male End</p>  <p>631 (S631) From: 15 x 1/2" x 15 To: 22 x 3/4" x 22</p>	<p>Tee with Male Threaded End</p>  <p>645 From: 1/2" x 1/2" x 15 To: 1/2" x 1/2" x 15</p>	<p>Tee with Female End</p>  <p>684 (S684) From: 15 x 1/2" x 15 To: 22 x 1/2" x 22</p>	<p>Stop End</p>  <p>323 (S323) From: 8mm To: 54mm</p>	<p>Cross - Equal</p>  <p>901 From: 22 x 22 x 22 x 22 To: 22 x 22 x 22 x 22</p>	<p>S Code is for DZR fittings</p> 	

*Les produits Conex/Bänninger sont certifiés par de nombreuses Autorités et Laboratoires de certification. Pour plus de détails sur cette gamme de produit, vous pouvez contacter par email notre équipe technique au : technical@ibpgroup.com

Conex Bänninger France - 17, rue de l'Hôtel de Ville - 92200 Neuilly-sur-Seine | Tel: +33 967 579 554
Email: salesfrance@ibpgroup.com | Website: <http://www.conexbanninger.com>

IBP Atcosa, S.L., Polígono industrial Quintos Aeropuerto, Apdo de Correos N°16 - 14080 CORDOBA | Tel : sales +34 957 469 620 / +34 957 469 655 . Fax: +34 957 469 632
Email: sales.spain@ibpgroup.com; sales.africa@ibpgroup.com | Website: <http://www.conexbanninger.com>