

Conex Compression

Simple and versatile, the fitting of choice



Features and Benefits:

- They are manufactured in duplex brass and/or dezincification resistant (DZR) brass.
- Conex Compression fittings are compatible with EN1057 equivalent copper tube to EN1057.
- Used in plumbing and heating applications.
- All fittings are manufactured in accordance with EN 1254-2 and 4.
- Suitable for Flame Free installations.
- PTFE tape is not required for installation.
- Installation with Polybutylene and Pex requires liners recommended by the tube manufacturer or supplied by Conex Bänninger.
- Kiwa and DVGW approved.



Conex Compression

Conex Compression range compatible with copper tube, polybutylene and PEX.

Straight Coupler



301
From: 10mm
To: 54mm

Male Straight Connector



302
From: 10mm
To: 54mm

Female Straight Connector



303
From: 10mm
To: 54mm

Stop End



323
From: 10mm
To: 54mm

Elbow



401
From: 10mm
To: 54mm

Male Elbow



402
From: 10mm
To: 54mm

Female Elbow



403
From: 10mm
To: 54mm

Female Wall Plate Elbow



403WL
From: 10mm
To: 22mm

Tee - Equal



601
From: 10mm
To: 54mm

Tee - Reducing



601
From: 22 x 22 x 10mm
To: 54 x 54 x 42mm

Tee - FI



617
From: 10mm
To: 22mm



*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: salesuk@ibpgroup.co.uk | Website: www.conexbanninger.com