

Conex | Bänninger Push-Fit

A Range of easy to use Conex Push-Fit fittings



















Features and Benefits:

- Suitable for hot and cold drinking water, heating and chilled water systems.
- Dezincification resistant (DZR) body in natural brass finish.
- Only two internal components: High grade EPDM O-Ring and Stainless Steel grab ring.
- Precision machined body with inbuilt tube stabiliser.
- Connects multiple tubes: copper, carbon steel, stainless steel, PB, PE-X.
- Professional tool for demounting, fittings can then be reused.
- Unique grab ring ensures the fitting is firmly orientated but not fixed, allowing turning for system alignment.
- Patented design.
- Maintains electrical continuity on metallic pipe systems.
- Stylish slim-line design for tight corners and exposed pipework.
- Fast and easy to install.
- Available in sizes 10, 12, 15, 18, 22 and 28mm.
- Flame free installation.
- One fitting for many tubes reduces toolbox weight and inventory costs.
- Conforms to normal operating parameters for metallic tubes: maximum working pressure of 16 bar at 30°C and 6 bar 95°C.
- Fitting can be recycled at end of life.
- 25 years guarantee.



Push-Fit Range

<p>Straight Connector</p>  <p>270 From: 10mm To: 28mm</p>	<p>Reduced Connector</p>  <p>240 From: 15 x 10mm To: 22 x 15mm</p>	<p>Fitting Reducer</p>  <p>243 From: 15 x 10mm To: 28 x 22mm</p>	<p>Elbow</p>  <p>090 From: 10mm To: 28mm</p>	<p>Street Elbow</p>  <p>001 From: 15mm To: 28mm</p>	<p>Straight Female Connector</p>  <p>270G From: 15 x 1/2" To: 28 x 1"</p>
<p>Straight Male Connector</p>  <p>243G From: 15 x 1/2" To: 28 x 1"</p>	<p>Straight Tap Connector</p>  <p>240G From: 15 x 1/2" To: 22 x 3/4"</p>	<p>Bent Tap Connector</p>  <p>002G Size: 15 x 1/2"</p>	<p>Wall Plate Elbow</p>  <p>472G Size: 15 x 1/2"</p>	<p>Tank Connector</p>  <p>350 From: 15 x 1/2" To: 28 x 1"</p>	<p>Equal Tee</p>  <p>130EQ From: 10mm To: 28mm</p>
<p>Reduced Branch Tee</p>  <p>130RB From: 22 x 22 x 15mm To: 28 x 28 x 22mm</p>	<p>Reduced End Tee</p>  <p>130RE Size: 15 x 10 x 15mm To: 28 x 22 x 28mm</p>	<p>Reduced End & Branch Tee</p>  <p>130REB Size: 22 x 15 x 15mm To: 28 x 22 x 22mm</p>	<p>Female Branch Tee Parallel Thread</p>  <p>130G Size: 15 x 15 x 1/2"</p>	<p>Stop End</p>  <p>301 From: 10mm To: 28mm</p>	<p>Release Tool & Head Pack</p>  <p>CP-FSET002 Size: 10, 15, 22 & 28mm head units & case</p>
<p>Tool Heads</p>  <p>CP-F Head From: 10mm To: 28mm</p>	<p>Internal Liners (for plastic pipes)</p>  <p>PP From: 10mm To: 28mm</p>				



*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: technical@ibpgroup.com.

Conex Universal Limited: Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.
 Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: salesuk@ibpgroup.co.uk | Website: www.ibpgroup.com