conex Bänninger

The >B< Press Inox Stainless Steel range is an innovative press system which is quick and simple to install providing a secure fitting.



Features and Benefits:

- >B< Profile 3 point press ensures a leak free, secure and permanent joint*.
- The leading edge design ensures that the pipe is parallel to the fitting before contact with the o-ring greatly reducing the chance of damaging the o-ring during assembly.
- >B< Press has a high quality o-ring with a reduced section on two positions causing leaks at low pressure when not pressed (from 0.1 bar). When the fitting is pressed, the o-ring material compresses itself to form a secure leak free joint.
- Flame free for ensuring no hot works and on site safety.
- Available in 12mm to 108mm.

- Un-pressed joints can be identified and corrected quickly without the need to drain the system down; making >B<
 Press a very quick and simple fitting to install, saving time and money.
- Mechanical hexagonal press form; gives a clear visual indication that it has been successfully secured both mechanically and hydraulically ensuring no joint rotation.
- The >B< Profile is the approved Conex Bänninger designed press form and the fittings are also compatible with various tools and jaws. This ensures that majority of existing systems work fully with the >B< Profile.



*Only available on sizes 12 to 54mm

Conex | Bänninger >B< Press Inox

Slip Coupler

PS4275

From:

From: 15mm To: 108mm

Bend with Female

15mm x 1/2" 54mm x 2"

Bend with Female Tread

15mm x 1/2 54mm x 2"

>B< Press Inox range with Pressing Indicator





15mm 108mn







Fitting Reducer 18 x 15mm 108 x 89mr From: Street Bend



From: 15mm To: 108mn







From: 15mm To: 54mm



Female Straight Coupler S4270G 15mm x 1/2' 54mm x 2" From:

Obtuse Elbow



From: 15mm To: 108mm Tee with Female Branch





Cross Over Coupler Short

PS508

995040

From: 15mm To: 28mm

Obtuse Street Elbow



- · Manufactured from stainless steel.
- Specially designed EPDM o-ring making >B< Press Inox suitable for HVAC, hot & cold and drinking water applications.
- Available in sizes 12 108mm.
- >B< Press Inox tube system available using precision steel tubes according to EN 10312.
- · Designed for hydrostatic water pressure up to 16 bar.
- Designed for temperature ranges of -35°C to 110°C.
- Fully tested to 40 bar.
- Full system available with approved >B< Inox tubes. System guarantee is 10 years.
- Fittings guarantee is 5 years when used with tubes in accordance with EN 10312.

*Les produits Conex/Bänninger sont certifies par de nombreuses Autorités et Laboratoires de certification. Pour plus de détails sur cette gamme de produit, vous pouvez contacter par email notre équipe technique au : technical@ibpgroup.com

Conex Bänninger France - 17, rue de l'Hôtel de Ville - 92200 Neuilly-sur-Seine | Tel: +33 967 579 554 Email: salesfrance@ibpgroup.com | Website: http://www.conexbanninger.com

IBP Atcosa, SL., Polígono industrial Quintos Aeropuerto, Apdo de Correos Nº16 - 14080 CORDOBA | Tel : sales +34 957 469 620 / +34 957 469 655 . Fax: +34 957 469 632 Email: sales.spain@ibpgroup.com; sales.africa@ibpgroup.com | Website: http://www.conexbanninger.com